



Undercounter dishwasher double skin with drain pump 50x50 - 400 V

Model SAP Code 00011287



- Display type: ProScreen 4 digit display + 2 LED bars
- Number of programs: 8
- Number of skin: 2
- Door clear height [mm]: 465
- Rack size [mm]: 500 x 500
- Water consumption of the washing cycle: 1,8
- Washing cycle time [s]: 60-90-180
- Detergent and rinse pump system: ProDose accurate dosing with a peristaltic pump
- Wash pump type: two-way DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ArchiMedes double filtration with overflow discharge ensures only 18% loss of clean water to waste

SAP Code	00011287	Boiler power [kW]	6.000
Net Width [mm]	600	Basin volume [l]	15
Net Depth [mm]	600	Tank power [kW]	1.400
Net Height [mm]	820	Water consumption of the washing cycle	1,8
Net Weight [kg]	55.00	Washing cycle time [s]	60-90-180
Power electric [kW]	7.900	Door clear height [mm]	465
Loading	400 V / 3N - 50 Hz	Rack size [mm]	500 x 500
Boiler capacity [l]	6.00	Noise of device	59,3





Technical drawing

Undercounter dishwasher double skin with drain pump 50x50 - 400 V

Model SAP Code 00011287











Undercounter dishwasher double skin with drain pump 50x50 - 400 V

Model SAP Code 00011287

Stainless steel outer shell construction

round construction with stainless steel, rounded edges, Deep-drawn bathtub

easy cleaning, high hygiene standard, long service life

Washing arms with a component, common for washing and rinsing

upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

easy and safe handling during cleaning; higher user comfort

LED Display

proScreen 4 local display + 2 LED strips

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

Double pump

unique two-way DuoFlow pump

 distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump

Molded basket supports

guide rails for the baskets molded from the body of the dishwasher

- high hygiene standard
- longer service life

Detergent dispensers

two detergent and rinse aid dispensers

 precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

Double filter system

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

higher washing efficiency; longer life of the washing bath

Energy saving

energy saving energy saving system due to lowering the temperature of the boiler

cost saving

Protection of fragile dishes

softstart system for gradual start of washing programs to protect fragile dishes

- protects stemmed glasses and other fragile utensils

Double shell construction

stainless steel construction with insulated double jacket

- quiet operation
- energy saving

Fast heating

performance management allows the current running of the boiler and basins body

- quick first warm-up of the dishwasher
- smooth operation

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com

2024-05-10

3



Technical parameters

Undercounter dishwasher double skin with drain pump 50x50 - 400 V				
Model SAP Code	00011287			
1. SAP Code: 00011287	15. Number of programs:			
2. Net Width [mm]: 600	16. Opening of device: Tilting down			
3. Net Depth [mm]: 600	17. Door clear height [mm]: 465			
4. Net Height [mm]: 820	18. Inlet pressure: 2-4bar			
5. Net Weight [kg]: 55.00	19. Adjustable feet: Yes			
6. Gross Width [mm]: 650	20. Number of skin:			
7. Gross depth [mm]: 650	21. Self-cleaning cycle: Yes			
8. Gross Height [mm]: 870	22. Boiler capacity [l]: 6.00			
9. Gross Weight [kg]: 63.00	23. Boiler power [kW]: 6.000			
10. Device type: Electric unit	24. Basin volume [l]: 15			
11. Control type: Digital	25. Tank power [kW]: 1.400			
12. Material: Stainless steel	26. Number of arms for both rinsing and washing:			
13. Power electric [kW]: 7.900	27. Arm connection: Click-clack - easy removal with one hand			

14. Loading:

400 V / 3N - 50 Hz

28. Washing arm type:

Rotatable two-pronged





Undercounter dishwasher double skin with drain pump 50x50 - 400 V					
Model SAP Code	00011287				
29. Washing arm material: Composite	41. Heating system: HotWash - System of simultaneous operation of the heating				
	element of the bath and the boiler, reducing the time for starting the next cycle				
30. Rinsing arm type: Rotating two-pronged	42. Hot water electric valve: Yes				
31. Rinsing arm material: Composite	43. Closing door system: ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes				
32. Deep drawn tank: Yes	44. Rack size [mm]: 500 × 500				
33. Rack support: Pressed	45. Display type: ProScreen - 4 digit display + 2 LED bars				
34. Tank surface strainers: composite	46. USB port: Yes, for Firmware actualisation				
35. Drain filter: ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste	47. Drain pump: Yes				
36. Thermostop: Yes	48. Self-diagnostics: Yes				
37. Boiler thermostat adjust: Yes	49. Wash pump type: two-way - DuoFlow				
38. Rack feed capacity: 60-40-20	50. Detergent dispenser: Yes				
39. Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump	51. Rinse aid dispenser: Yes				

40. Energy Saving system:

boiler temperature

EnergySaving - Energy saving system due to lowering the

1,8

52. Water consumption of the washing cycle:



Technical parameters

Undercounter dishwasher double skin with drain pump 50x50 - 400 V					
Model	SAP Code	00011287			
53. Washing cycle time [s]: 60-90-180		60. Program ProClean: Yes			
54. Rinse water temperature [°C]: 80		61. Program ProDrain: Yes			
55. Standard equipment for device: 1x glass basket, 1x plate basket, 1x cutlery basket		62. Program ProEco: Yes			
56. Additional information: The product comes with 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273) for free		63. Program ProLong: Yes			
57. Program ProSpeed: Yes		64. Program ProGlass: Yes			
58. Program ProFessional: Yes		65. Noise of device: 59,3			

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com

59. Program ProTemp:

Yes