

# Technical data sheet



## Product features

### Undercounter dishwasher single skin with drain pump 35x35 - 230 V

<b>Model</b>	<b>SAP Code</b>	00011264
--------------	-----------------	----------



- Display type: 3 local display + diode bar
- Number of programs: 5
- Number of skin: 1
- Door clear height [mm]: 260
- Rack size [mm]: 350 x 350
- Water consumption of the washing cycle: 1,6
- Washing cycle time [s]: 60-120-150
- Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump
- Wash pump type: two-way - DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

<b>SAP Code</b>	00011264	<b>Boiler power [kW]</b>	2.600
<b>Net Width [mm]</b>	401	<b>Basin volume [l]</b>	7
<b>Net Depth [mm]</b>	490	<b>Tank power [kW]</b>	0.600
<b>Net Height [mm]</b>	595	<b>Water consumption of the washing cycle</b>	1,6
<b>Net Weight [kg]</b>	28.00	<b>Washing cycle time [s]</b>	60-120-150
<b>Power electric [kW]</b>	3.500	<b>Door clear height [mm]</b>	260
<b>Loading</b>	230 V / 1N - 50 Hz	<b>Rack size [mm]</b>	350 x 350
<b>Boiler capacity [ l ]</b>	2.60	<b>Noise of device</b>	61

# Technical data sheet





Technical drawing

Undercounter dishwasher single skin with drain pump 35x35 - 230 V

Model

SAP Code

00011264



### Undercounter dishwasher single skin with drain pump 35x35 - 230 V

<b>Model</b>	<b>SAP Code</b>	00011264
--------------	-----------------	----------

**1** **Stainless steel outer shell construction**  
round construction with stainless steel, rounded edges, partially pressed tub

- easy cleaning, high hygiene standard, long service life

**2** **Washing arms with a component, common for washing and rinsing**  
washing arms made of composite material  
common arm for washing and rinsing  
integrated screw secured against falling out

- easy and safe handling during cleaning; higher user comfort

**3** **LED Display**  
three-line display  
diode strip

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

**4** **Double pump**  
unique two-way DuoFlow pump

- distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump

**5** **Molded basket supports**  
guide rails for the baskets molded from the body of the dishwasher

- high hygiene standard
- longer service life

**6** **Detergent dispensers**  
two detergent and rinse aid dispensers

- precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

**7** **Double filter system**  
the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

- higher washing efficiency; longer life of the washing bath

**8** **Energy saving**  
energy saving energy saving system due to lowering the temperature of the boiler

- cost saving

# Technical data sheet



## Technical parameters

### Undercounter dishwasher single skin with drain pump 35x35 - 230 V

<b>Model</b>	<b>SAP Code</b>	00011264
--------------	-----------------	----------

**1. SAP Code:**

00011264

**15. Number of programs:**

5

**2. Net Width [mm]:**

401

**16. Opening of device:**

Tilting down

**3. Net Depth [mm]:**

490

**17. Door clear height [mm]:**

260

**4. Net Height [mm]:**

595

**18. Inlet pressure:**

2-4bar

**5. Net Weight [kg]:**

28.00

**19. Adjustable feet:**

Yes

**6. Gross Width [mm]:**

451

**20. Number of skin:**

1

**7. Gross depth [mm]:**

540

**21. Self-cleaning cycle:**

Yes

**8. Gross Height [mm]:**

645

**22. Boiler capacity [ l ]:**

2.60

**9. Gross Weight [kg]:**

31.00

**23. Boiler power [kW]:**

2.600

**10. Device type:**

Electric unit

**24. Basin volume [l]:**

7

**11. Control type:**

Digital

**25. Tank power [kW]:**

0.600

**12. Material:**

AISI 304

**26. Number of arms for both rinsing and washing:**

2

**13. Power electric [kW]:**

3.500

**27. Arm connection:**

Hand loosen/tighten screw

**14. Loading:**

230 V / 1N - 50 Hz

**28. Washing arm type:**

Rotatable two-pronged

# Technical data sheet



## Technical parameters

### Undercounter dishwasher single skin with drain pump 35x35 - 230 V

<b>Model</b>	<b>SAP Code</b>	00011264
--------------	-----------------	----------

**29. Washing arm material:**

Composite

**30. Rinsing arm type:**

Rotating two-pronged

**31. Rinsing arm material:**

Composite

**32. Rack support:**

Pressed

**33. Tank surface strainers:**

composite

**34. Drain filter:**

ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

**35. Thermostop:**

Yes

**36. Boiler thermostat adjust:**

Yes

**37. Rack feed capacity:**

24-30-60

**38. Detergent and rinse pump system:**

ProDose - accurate dosing with a peristaltic pump

**39. Energy Saving system:**

EnergySaving - Energy saving system due to lowering the boiler temperature

**40. Rack size [mm]:**

350 x 350

**41. Display type:**

3 local display + diode bar

**42. USB port:**

Yes, for Firmware actualisation

**43. Drain pump:**

Yes

**44. Self-diagnostics:**

Yes

**45. Wash pump type:**

two-way - DuoFlow

**46. Detergent dispenser:**

Yes

**47. Rinse aid dispenser:**

Yes

**48. Water consumption of the washing cycle:**

1,6

**49. Washing cycle time [s]:**

60-120-150

**50. Rinse water temperature [Å°C]:**

65

**51. Standard equipment for device:**

2x glass basket, 1x cutlery basket

**52. Program ProSpeed:**

Yes

**53. Program ProFessional:**

Yes

**54. Program ProTemp:**

Yes

# Technical data sheet



Technical parameters

Undercounter dishwasher single skin with drain pump 35x35 - 230 V

<b>Model</b>	<b>SAP Code</b>	00011264
--------------	-----------------	----------

**55. Program ProClean:**

Yes

**57. Noise of device:**

61

**56. Program ProDrain:**

Yes